

## 16 SEER SINGLE-STAGE COMMUNICATING HEAT PUMP

1½ THRU 5 TONS SPLIT SYSTEM

208 / 230 Volt, 1-phase, 60 Hz

### REFRIGERATION CIRCUIT

- Scroll compressors on all models
- Suction line accumulator factory installed
- Bi-flow filter-drier supplied with every unit for field installation
- Integrated solid state control with Time-Temperature Defrost
- External high and low refrigerant service ports
- Copper tube/aluminum fin coil



TSTAT0201CW




### PERFORMANCE

- Communicating, self-configuring operation control
- Outdoor temperature sensor factory installed
- Compressor sound blanket standard
- Isolation compressor grommets

### EASY TO INSTALL AND SERVICE

- Text based diagnostics with control
- Easy access service valves on all models
- Innovative control box design
- High and low pressure switches
- Only two screws to access control panel
- Factory charged with R-410A refrigerant



### BUILT TO LAST

- High gloss, baked-on powder coat finish over galvanized steel
- Post-painted (black) coil fins
- Coated, weather-resistant cabinet screws
- Coated inlet grille with 3/8" (10mm) spacing for extra protection (hail guard)
- Corner posts for extra strength and style

### WARRANTY\*

- 5 year No Hassle Replacement™ limited warranty
- 5 year parts limited warranty (including compressor and coil)
  - With timely registration, an additional 5 year parts limited warranty (including compressor and coil)

\* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



Qualifying models only

This product has been designed and manufactured to meet ENERGY STAR criteria for energy efficiency when matched with appropriate coil components. However, proper refrigerant charge and proper air flow are critical to achieve rated capacity and efficiency. Installation of this product should follow the manufacturer's refrigerant charging and air flow instructions. Failure to confirm proper charge and airflow may reduce energy efficiency and shorten equipment life.



Use of the AHRI Certified™ Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to [www.ahridirectory.org](http://www.ahridirectory.org).

UNIT PERFORMANCE DATA							
Model Number	Size (tons)	Nominal Btu/hr	Min. Circuit Ampacity	Max. Fuse or Breaker	Operating Dimensions height x width x depth in. (mm)	Ship / Operating Weight lbs. (kg)	Notes
CSH618GKA	1½	18,000	13.6	20	"31-3/16 x 31-3/16 x 35-1/2 (792.5 x 792.5 x 902.0) "	"213 / 181 (96.6 / 82.1) "	
CSH624GKA	2	24,000	15.5	25	" 35 x 35 x 33-5/8 (889.0 x 889.0 x 853.5) "	"232 / 194 (105.2 / 88.0) "	
CSH630GKA	2½	30,000	19.9	30	" 35 x 35 x 33-5/8 (889.0 x 889.0 x 853.5) "	"267 / 229 (121.1 / 103.9) "	
CSH636GKA	3	36,000	21.6	35	" 35 x 35 x 33-5/8 (889.0 x 889.0 x 853.5) "	"275 / 237 (124.7 / 107.5) "	
CSH642GKA	3½	42,000	27.8	40	" 35 x 35 x 33-5/8 (889.0 x 889.0 x 853.5) "	"293 / 255 (132.9 / 115.7) "	
CSH648GKA	4	48,000	31.8	45	" 35 x 35 x 33-5/8 (889.0 x 889.0 x 853.5) "	"298 / 260 (135.2 / 117.9) "	
CSH660GKA	5	60,000	33.9	50	" 35 x 35 x 47-3/16 (889.0 x 889.0 x 1199.0) "	"363 / 317 (164.7 / 143.8) "	