

R-410A GEOTHERMAL SPLIT HEAT PUMP 2 TO 5 TON

EASIER TO SELL

- 3.4 - 4.5 COP, 15.4 - 26.4 EER (Closed Loop)
- 3.9 - 5.1 COP, 19.2 - 30.5 EER (Open Loop)
- Compressor blanket
- Fully insulated cabinet with closed cell foam
- Optional supplemental domestic water heating

TOUGHER

- Two-stage scroll compressor
- Used with variable speed fan coil or furnace coil

EASIER TO INSTALL AND SERVICE

- Unit compatible with ICP evaporator coils
- Compatible with FVM4X Fan Coils
- Microprocessor control
- Compatible with many 3 stage heat, 2 stage cooling programmable thermostats

WARRANTY *

- 5 year No Hassle Replacement™ limited warranty
 - 5 year labor limited warranty
 - With timely registration, an additional 5 year labor limited warranty
 - 10 year labor limited warranty (including compressor)
- * For residential applications only (owner occupied for No Hassle Replacement™ warranty). See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



This product has been designed and manufactured to meet ENERGY STAR criteria for energy efficiency when matched with appropriate coil components. However, proper refrigerant charge and proper air flow are critical to achieve rated capacity and efficiency. Installation of this product should follow the manufacturer's refrigerant charging and air flow instructions. Failure to confirm proper charge and airflow may reduce energy efficiency and shorten equipment life.



Use of the AHRI Certified™ Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.

Model Number	Size (ton)	Nominal BTU/hr	Min. Circuit Amps	Max. Fuse/ Brkr	Dimensions H x W x D (in)	Operating (Shipping) Wt - Lbs	Notes
HS024SXXCDXX1XX1	2	24000	14.60	25	21.5 x 24 x 27.4	189 (172)	
HS024SXXCXXX1XX1	2	24000	14.60	25	21.5 x 24 x 27.4	189 (172)	
HS024SXXNDXX1XX1	2	24000	14.60	25	21.5 x 24 x 27.4	189 (172)	
HS024SXXNXXX1XX1	3	36000	19.10	30	21.5 x 24 x 27.4	189 (172)	
HS036SXXCDXX1XX1	3	36000	19.10	30	21.5 x 24 x 27.4	189 (172)	
HS036SXXCXXX1XX1	3	36000	19.10	30	21.5 x 24 x 27.4	189 (172)	
HS036SXXNDXX1XX1	3	36000	19.10	30	21.5 x 24 x 27.4	189 (172)	
HS036SXXNXXX1XX1	3	36000	19.10	30	21.5 x 24 x 27.4	189 (172)	
HS048SXXCDXX1XX1	4	48000	26.50	45	21.5 x 24 x 27.4	189 (172)	
HS048SXXCXXX1XX1	4	48000	26.50	45	21.5 x 24 x 27.4	189 (172)	
HS048SXXNDXX1XX1	4	48000	26.50	45	21.5 x 24 x 27.4	189 (172)	
HS048SXXNXXX1XX1	4	48000	26.50	45	21.5 x 24 x 27.4	189 (172)	
HS060SXXCDXX1XX1	5	60000	33.90	60	23.3 x 27 x 33.4	261 (237)	
HS060SXXCXXX1XX1	5	60000	33.90	60	23.3 x 27 x 33.4	261 (237)	
HS060SXXNDXX1XX1	5	60000	33.90	60	23.3 x 27 x 33.4	261 (237)	
HS060SXXNXXX1XX1	5	60000	33.90	60	23.3 x 27 x 33.4	261 (237)	